

Hardware Notes - Pro/ENGINEER Wildfire 4.0

Last updated: May 31, 2007

- [Platform Support](#)
- [System Requirements](#)
- [Language Support](#)
- [Graphics Information](#)
- [Certified and Supported Graphics Cards](#)
- [Supported Peripherals and Accessories](#)
- [Supported MCAD Systems](#)
- [Supported Finite Element Solvers](#)
- [Supported Data Transfer Standards](#)

Platform Support			
Partner	Platform	Operating System levels	CPU
Hewlett-Packard	HP-UX (64-bit only)	11iV1 ^a	PA8000 or later
Microsoft ▪ Dell ▪ Fujitsu-Siemens ▪ Hewlett-Packard ▪ IBM ▪ Lenovo ▪ Sun	Windows Vista Business Edition Windows Vista Ultimate Edition	Base OS	Intel Pentium/Xeon/Core Duo/Core 2 Duo family
	Windows XP Professional x64 Edition	Base OS, Service Pack 2	Intel Pentium/Xeon/Core Duo/Core 2 Duo family AMD Opteron family
	Windows XP Professional Edition; Windows XP Home Edition	Base OS, Service Pack 1 and 2	Intel Pentium/Xeon/Core Duo/Core 2 Duo family AMD Opteron family
Sun	Solaris (64-bit only)	8 and 10	UltraSPARC II or later
	Solaris (64-bit only)	10	AMD Opteron family
NOTES			
^a The command "uname -a" returns "HP-UX 11.11"			

System Requirements					
		Windows XP, Vista		UNIX	
		Minimum	Recommended	Minimum	Recommended
Main Memory		256 MB	1024 MB or higher	256 MB	1024 MB or higher
Available Disk Space	Pro/ENGINEER	2.0 GB	2.5 GB or higher ^a	2.5 GB	3.0 GB or higher
	Pro/ENGINEER with Pro/ENGINEER Mechanical Wildfire 4.0	2.0 GB	3.0 GB or higher ^a	3.0 GB or higher	3.5 GB or higher
Swap Space		500 MB	2048 MB or higher	500 MB	2048 MB or higher
CPU speed		500 MHz	2.4 GHz or higher	See above table for individual vendor processor support	
Internal Browser Support		Microsoft Internet Explorer 7.0 Microsoft Internet Explorer 6.0 (SP1 or later)		Browser (Mozilla 1.7.8) is embedded in Pro/Engineer on UNIX platform	
Monitor		1024 x 768 (or higher) resolution support with 24-bit or greater color		1024 x 768 (or higher) resolution support with 24-bit or greater color	

Network	Microsoft TCP/IP Ethernet Network Adapter	TCP/IP Ethernet Network Adapter
Mouse	Microsoft-approved 3-button mouse	3-button mouse
File systems	NTFS	All vendor-supported file systems.
Misc.	CD-ROM or DVD drive	CD ROM or DVD drive
NOTES		
^a For Windows XP only. For 32-bit operating systems, the Windows limit is 2.0GB. For Windows XP you must enable the /3GB switch in order to utilize RAM greater than 2.0GB.		

Language Support			
Supported Language	Date Certified	Release Datecode	Comments
English	13-Jun-2007	C000	
Chinese Simplified	13-Jun-2007	C000	
Chinese Traditional		F000	Will be available with the production shipment of Pro/ENGINEER Wildfire 4.0 in early 2008.
French		F000	Will be available with the production shipment of Pro/ENGINEER Wildfire 4.0 in early 2008.
German	13-Jun-2007	C000	
Italian		F000	Will be available with the production shipment of Pro/ENGINEER Wildfire 4.0 in early 2008.
Korean		F000	Will be available with the production shipment of Pro/ENGINEER Wildfire 4.0 in early 2008.
Japanese	13-Jun-2007	C000	
Spanish		F000	Will be available with the production shipment of Pro/ENGINEER Wildfire 4.0 in early 2008.
NOTES			
For more detailed information on localization for this product, please click here .			

Graphics Information

For 3D-hardware acceleration, an OpenGL graphics card must be used that has been tested in a PTC-certified configuration. To ensure the compatibility of a graphics driver with Pro/ENGINEER Wildfire 4.0, a PTC-certified hardware configuration is recommended.

Dual Monitor Support

Limited dual monitor support is provided in Pro/ENGINEER Wildfire 4.0 on the Windows platform. PTC has successfully performed limited testing of some graphics card models from 3DLabs, ATI and NVIDIA that support dual monitor capabilities. If your graphics card is certified for Pro/ENGINEER Wildfire 4.0 and provides dual monitor support**, PTC expects that it will run in this mode without issue. PTC will provide limited support to resolve issues arising when running in dual monitor mode, however, the entire solution will not be submitted for formal certification as a complete configuration.

Note: in the event that dual monitor mode fails, we advise use of Span mode as a workaround.

**Please consult with AMD, NVIDIA, or the hardware platform partner to confirm the availability of this functionality with a given graphics card that has been certified with Pro/ENGINEER Wildfire 4.0.

Certified and Supported Graphics Cards

PTC provides Customer Support for all certified and/or supported graphics cards. Certified cards will be added to this table as our platform partners complete certifications in preparation for production shipment of Wildfire 4.0.

Please note that the table below represents graphics cards that are part of a fully-certified or supported configuration (e.g., machine, model, operating system, graphics card and driver). PTC does not certify or support graphic cards independently from the configurations in which they are certified or supported. Please consult the linked partner pages for specific configurations.

Supported Graphics Cards				
Partner	Certified Graphics Cards	Certification Details	Supported Graphics Cards	Support Details
AMD (ATI)			FireGL V7300	Fujitsu-Siemens
			FireGL V7200	Dell, HP
			FireGL V5250	Lenovo
			FireGL V5200	Fujitsu-Siemens, HP, Lenovo
			FireGL V3400	Dell, HP
			FireGL V3300	HP
NVIDIA			Quadro FX5500	HP, Sun
			Quadro FX4600	Dell
			Quadro FX4500	Dell, HP, Sun
			Quadro FX3500	Dell, Fujitsu-Siemens, HP, Sun
			Quadro FX3450	HP, Sun
			Quadro FX3400	Dell, HP
			Quadro FX3000	Sun
			Quadro FX2500	Dell
			Quadro FX1500M	HP
			Quadro FX1500	Dell, Fujitsu-Siemens, HP
			Quadro FX1400	HP, Sun
			Quadro FX1100	Sun
			Quadro FX560	HP
			Quadro FX550	Dell
			Quadro FX540	HP, Sun
Sun			XVR-1200	Sun

Supported Peripherals and Accessories

Windows (XP, XP
x64, Vista)

Sun Solaris

HP-UX

3D Controllers (Pro/ENGINEER only) Please refer to <http://www.3dconnexion.com/software/> for specific driver information.

SpaceTraveler

[Certified](#) [Certified](#)

[Certified](#)

SpaceBall 5000

[Certified](#) [Certified](#)

[Certified](#)

Plotters and Printers

Pro/ENGINEER supports HPGL, HPGL/2, PostScript, Calcomp, Gerber and Versatec standard plotting formats. In addition, Pro/ENGINEER supports the Microsoft Print Manager.

If you do not see your printer/plotter on the list below, please refer to the [Introduction and Support Policy](#).

Emulation

Various manufacturers produce printers and plotters that may be compatible with or emulate a device that is supported by PTC. Please be aware that such devices are not tested by PTC and therefore, may not produce correct plotted output. If you are using a device which emulates a printer or plotter listed in the tables below, PTC Technical Support will attempt to provide support by using a similar certified device. Any support pertaining to compatibility with a supported plotter or the correctness of an emulation can only be made by the manufacturers of the device in question, and not by PTC.

The Microsoft Printer Manager creates an emulation of what appears on the screen and attempts to print this. Since this emulation is between the Print Manager driver and the printer/plotter driver, quality and results may vary. You may choose to try a certified PTC printer/plotter driver, which has been optimized for high quality printing.

Plotters			
	Windows XP	Sun Solaris	HP-UX
HP Designjet 1055CM+	Certified	Certified	Certified
HP Designjet 800PS	Certified	Certified	Certified
HP Designjet 5500PS	Certified	Certified	Certified
HP Designjet copier cc800PS	Certified	Certified	Certified
HP Designjet 4000	Certified	Certified	Certified
Printers			
HP deskjet 1220cps	Certified	Certified	Certified
HP color inkjet cp1700ps	Certified	Certified	Certified
HP business inkjet 2600dn	Certified	Certified	Certified

Supported MCAD Systems

You can integrate several MCAD systems with Pro/ENGINEER Mechanica Wildfire 4.0. The following table lists the supported MCAD systems and platforms.

Platforms	CATIA Release 4.2.4 (English only)	Unigraphics Release NX 3.0 (English only)
HP (64 bit)	x	x
Intel-based PC (Windows XP)		x
Sun (64 bit)		x
NOTES		

Supported Finite Element Solvers

You can integrate several Finite Element Solvers with Pro/ENGINEER Mechanical Wildfire 4.0 for use in FEM mode. The following table lists the supported Finite Element Solvers and platforms.

Platforms	NASTRAN 2005 r2	ANSYS 10.0
HP (64 bit)	x	x
Intel-based PC (Windows XP)	x	x
Sun (64 bit)	x	x
NOTES		

Supported Data Transfer Standards

Pro/ENGINEER Mechanical Wildfire 4.0 supports the following standards for transferring data to and from MCAD programs:

Platform	DXF 13.0	IGES 5.2	VDA 2.0
HP (64 bit)	x	x	x
Intel-based PC (Windows XP)	x	x	
Sun (64 bit)	x	x	x